TATA MOTORS

TATA

BHAROSA
HAR KADAM >

PRESENTING THE NEW
TATA XENON YODHA BS IV.

THE RELIABLE PICKUP FOR YOUR BUSINESS.

XENON YODHA

SMS* 'XENON YODHA' TO 5616161

*Conditions apply.

FEATURE	XENON YODHA BS IV
ENGINE	
Type	Tata 4SPCR TCIC 4 cylinder BSIV
Capacity	2956 cm^3
Max. Output	64 kW (85 HP) @ 3000 r/min
Max. Torque	250 Nm @ 1000-2000 r/min
Fuel Tank Capacity	45 l
CLUTCH & TRANSMISSION	
Clutch	Single plate dry friction type 260 mm Dia
Gearbox	GBS 76 – 5/4.1
	Synchromesh 5 forward + 1 reverse
Steering	Power steering
SUSPENSION	
Front	Semi-Elliptical Leaf Springs - 6 leaves
Rear	Innovative two stage Semi-Elliptical Leaf Springs - 9 leaves
Anti-roll bar	Front
BRAKES	
Front	Hydraulic, twin pot Disc Brakes
Rear	Drum Brakes
WHEELS & TYRES	
Tyre	215/75 R 16 Radial
Rim size	16-Inch

OVERALL VEHICLE DIMENSIONS	
Width	1860 mm
Length	5350 mm
Height	1810 mm
Ground Clearance	210 mm
Wheel Base	3150 mm
Internal Load Body (LxB)	2550 mm (8.4 ft) x 1750 mm (5.7 ft)
Turning Circle Radius	6250 mm
WEIGHT (kg)	
GVW	3100
Kerb Weight	1850
Payload	1250
PERFORMANCE	
Gradeability	30%
Restart Gradeability	22%
Top Speed	80 km/h
Seating Capacity	D+1
WARRANTY TERMS	
Engine oil change interval	20 000 km
Warranty (On Driveline)	3 year or 3 Lakh km (whichever is earlier)

For more information contact: Tata Motors Limited, 4th Floor, CVBU, Ahura Centre, Mahakali Caves Road, Shanti Nagar, Andheri (E), Mumbai - 400093. Call: 1800 20 97979 (Toll-free), Visit: www.tatamotors.com or SMS*: <XENON YODHA> to 5616161.

The illustrations and photographs may show accessories and items of optional equipment which are not part of standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement.

#As per terms & conditions in the operator's service manual. *₹ 3 per SMS or as per service provider.